

# MATERIAL SAFETY DATA SHEET

Trade Name: **CuraPoxy® LS - Part A**

## SECTION I

**Manufacturer:** CuraFlo®  
23400 Commerce Park  
Beachwood, OH 44122

**Emergency Telephone #:** 703-527-3887  
Chemtrec

**Date:** May 1, 2008

**Information Telephone #:** 800-714-9259

## SECTION II: INGREDIENT INFORMATION

<u>INGREDIENT</u>	<u>CAS NUMBER</u>	<u>PEL</u>	<u>TLV</u>
Epoxy Resin	25068-38-6	N/E	N/E
Polyfunctional Glycidyl Ether Modifier	74398-71-3	N/E	N/E
Amorphous Silicon Dioxide	7631-86-9	*80 mg/m <sup>3</sup>	*3 mg/m <sup>3</sup>
Mica	12001-26-2	*3 mg/m <sup>3</sup>	*3 mg/m <sup>3</sup>
Titanium Dioxide	13463-67-7	*15 mg/m <sup>3</sup>	*10 mg/m <sup>3</sup>

N/E indicates "not established"

SARA Title III, Section 313 ingredients: None

All ingredients are TSCA inventory listed.

\*Note: The PEL & TLV for this ingredient are for respirable dust levels only. In this product, it is pre-dispersed and not available as a dust. Therefore, under normal use conditions it is not considered a hazard.

The specific identity and/or remaining ingredient(s) are being withheld as a trade secret.

## SECTION III: PHYSICAL DATA

**Boiling Point:** > 100 deg C

**Vapor Pressure:** Not available

**Vapor Density:** Not applicable

**Solubility in Water:** Negligible

**Appearance and Odor:** Heavy paint consistency - mild epoxy odor

**Specific Gravity:** 1.1 - 1.4

**Melting Point:** Not available

**Evaporation Rate:** Not established

**% Volatile by Volume:** <1%

## SECTION IV: FIRE & EXPLOSION HAZARD DATA

**Flash Point:** >100 deg C, TCC Method

**Extinguishing Media:** Foam, CO<sub>2</sub>, Dry Chemical, Water Spray

**Special Fire Fighting Procedures:** The use of self-contained breathing apparatus is recommended for firefighters. Water may be helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used for cooling purposes.

**Unusual Fire and Explosion Hazards:** Keep work areas free of hot metal surfaces and other sources of ignition.

**NFPA classification:** Health: 2 Flammability: 1 Reactivity: 0

**OSHA/NFPA Fire Hazard Classification:** Class III B

**LFL:** Not available **UFL:** Not available

## SECTION V: REACTIVITY DATA

**Stability:** Stable, will react with amines.

**Incompatibility:** Strong acids and bases, selected amines, oxidizing agents.

**Hazardous Decomposition or Byproducts:** Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, acids, aldehydes, ketones and other unidentified toxic and/or irritating compounds.

**Hazardous Polymerization:** Will not occur.

## **SECTION VI: HEALTH HAZARD DATA**

### **Primary Routes of Entry:**

**EYES:** May cause slight transient (temporary) eye irritation. Product may be irritating to the eyes.

**SKIN:** May cause allergic skin reaction in susceptible individuals. Prolonged exposure not likely to cause significant skin irritation. Repeated exposure may cause skin irritation. A single prolonged exposure is not likely to result in the material being absorbed through skin in harmful amounts.

**INHALATION:** Vapors are unlikely due to physical properties.

**INGESTION:** Single dose oral toxicity is low. No hazards anticipated from ingestion incidental to industrial exposure.

**SYSTEMIC and OTHER EFFECTS:** Except for skin sensitization, repeated exposures to low molecular weight epoxy resins of this type are not anticipated to cause any significant adverse effects.

**Carcinogenicity:** Contains no ingredient listed as a potential carcinogen or as a carcinogen per OSHA, ACGIH, NTP or IARC at concentrations equal to or greater than 0.1%.

### **Emergency and First Aid Procedures:**

**EYES:** Flush with large quantities of water for at least 15 minutes. Consult a physician.

**SKIN:** Wash thoroughly with soap and flowing water.

**INHALATION:** Remove to fresh air if effects occur. Consult a physician.

**INGESTION:** No adverse effects anticipated by this route of exposure incidental to proper industrial handling.

## **SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE**

**Steps to Be Taken in Case Material is Released or Spilled:** Keep sources of ignition and hot metal surfaces isolated from the spill. Material may flow slowly. Scrape into containers for disposal.

**Waste Disposal Methods:** Dispose of according to all local, state and federal regulations.

**Precautions to Be Taken in Handling and Storing:** Keep containers closed when not in use. Avoid prolonged or repeated contact with skin. DO NOT handle or store near flame, heat or strong oxidants. Do not store in direct sunlight. Avoid prolonged storage above 35 deg C.

## **SECTION VIII: CONTROL MEASURES**

**RESPIRATORY:** If exposure may or does exceed occupational exposure limits, respiratory irritation is experienced, or during spray application, use a properly fitted MSHA/NIOSH approved respirator fitted with organic vapor cartridges. In addition, spray application may require the use of paint pre-filters. If sanding or grinding on cured material, use above respirator fitted with HEPA filters or a dust mask.

**VENTILATION:** General mechanical ventilation is sufficient for most conditions. Local exhaust ventilation may be necessary for some operations.

**EYES:** Use safety glasses, splash-proof eye goggles or goggles with full faceshield.

**CLOTHING/GLOVES:** Use impermeable gloves to prevent skin irritation. If potential for skin contact is present, impervious protective clothing should be worn.

**OTHER PROTECTIVE EQUIPMENT:** The availability of eye washes and safety showers in work areas is recommended.

## **SECTION IX: TRANSPORT DATA**

**Proper Shipping Name:** Not regulated

**Hazard Class:** Not regulated

**Identification Number:** None

**Packing Group:** None

## **SECTION X: DISCLAIMER**

**CURAFLO MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO ANY INFORMATION PRESENTED HEREIN, ALL OF WHICH IS PROVIDED "AS IS". TO THE MAXIMUM EXTENT PERMITTED BY LAW, CURAFLO EXPRESSLY EXCLUDES ALL WARRANTIES, OBLIGATIONS, REPRESENTATIONS, LIABILITIES, TERMS AND CONDITIONS (WHETHER THEY ARE EXPRESS OR IMPLIED, OR ARISE IN CONTRACT, STATUTE, OR OTHERWISE, AND IRRESPECTIVE OF THE NEGLIGENCE OF CURAFLO, ITS EMPLOYEES OR AGENTS) IN CONNECTION WITH THE INFORMATION PRESENTED HEREIN. CURAFLO MAKES NO REPRESENTATIONS OR WARRANTIES AS TO MERCHANTABILITY, FITNESS FOR PURPOSE, NONINFRINGEMENT OR CONFORMITY WITH DESCRIPTION OR SAMPLE.**

# MATERIAL SAFETY DATA SHEET

**Trade Name: CuraPoxy® LS - Part B**

## SECTION I

**Manufacturer:** CuraFlo®  
23400 Commerce Park  
Beachwood, OH 44122

**Emergency Telephone #:** 703-527-3887  
Chemtrec

**Date:** July 1, 2007

**Information Telephone #:** 800-714-9259

**Reason for Revision:** New MSDS

## SECTION II: INGREDIENT INFORMATION

<u>INGREDIENT</u>	<u>CAS NUMBER</u>	<u>PEL</u>	<u>TLV</u>
Isophoronediamine	2855-13-2	N/E	N/E
Modified cycloaliphatic amine	trade secret	N/E	N/E
Amorphous Silicon Dioxide	7631-86-9	*80 mg/m <sup>3</sup>	*3 mg/m <sup>3</sup>
Mica	12001-26-2	*3 mg/m <sup>3</sup>	*3 mg/m <sup>3</sup>

N/E indicates "not established"

SARA Title III, Section 313 ingredients: None

All ingredients are TSCA inventory listed.

\*Note: The PEL & TLV for this ingredient are for respirable dust levels only. In this product, it is pre-dispersed and not available as a dust. Therefore, under normal use conditions it is not considered a hazard.

The specific identity and/or remaining ingredient(s) are being withheld as a trade secret.

## SECTION III: PHYSICAL DATA

**Boiling Point:** > 100 deg C

**Vapor Pressure:** Not available

**Vapor Density:** Not applicable

**Solubility in Water:** Negligible

**Appearance and Odor:** Heavy paint consistency – slight ammonia odor

**Specific Gravity:** 1.1 - 1.4

**Melting Point:** Not available

**Evaporation Rate:** Not established

**% Volatile by Volume:** <1%

## SECTION IV: FIRE & EXPLOSION HAZARD DATA

**Flash Point:** >100 deg C, TCC Method

**Extinguishing Media:** Foam, CO<sub>2</sub>, Dry Chemical, Water Spray

**Special Fire Fighting Procedures:** The use of self-contained breathing apparatus is recommended for firefighters. Water may be helpful in keeping adjacent containers cool.

**Unusual Fire and Explosion Hazards:** Keep work areas free of hot metal surfaces and other source of ignition.

**NFPA classification:** Health: 3 Flammability: 1 Reactivity: 0

**OSHA/NFPA Fire Hazard Classification:** Class III B

**LFL:** Not available

**UFL:** Not available

## SECTION V: REACTIVITY DATA

**Stability:** Stable

**Incompatibility:** Strong acids and bases, selected epoxy resins and strong oxidizing agents.

**Hazardous Decomposition or Byproducts:** Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, ammonia, nitrogen oxides and other unidentified toxic and/or irritating compounds.

**Hazardous Polymerization:** Will not occur.

## **SECTION VI: HEALTH HAZARD DATA**

### **Primary Routes of Entry:**

**EYES:** Severe eye irritant. May cause burns. Vapors may be irritating.

**SKIN:** Severe skin irritant. May cause injury to skin following prolonged or repeated contact. Repeated exposure may cause sensitization of the individual.

**INHALATION:** Vapors/mists may be corrosive to the upper respiratory tract. Repeated or prolonged exposure can result in lung damage. May cause respiratory tract sensitization.

**INGESTION:** Not expected to be a relevant route of exposure. However, the material is corrosive and may cause permanent damage to the mouth, throat and stomach.

**SYSTEMIC and OTHER EFFECTS:** Product can be alkaline, corrosive and irritating to skin, ears, eyes and mucous membranes. May cause injury upon prolonged contact and repeated contact.

**Carcinogenicity:** Contains no ingredient listed as a potential carcinogen or as a carcinogen per OSHA, ACGIH, NTP or IARC at concentrations equal to or greater than 0.1%.

### **Emergency and First Aid Procedures:**

**EYES:** Flush with large quantities of water for at least 15 minutes. Seek immediate medical attention.

**SKIN:** Wash immediately with soap and water. If irritation or sensitization occurs, remove individual from further contact with material. Remove and wash contaminated clothing before reuse.

**INHALATION:** Remove to fresh air if effects occur. Consult a physician.

**INGESTION:** If this product is swallowed, administer 3-4 glasses of milk or water. Do not induce vomiting. Seek medical advice.

## **SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE**

**Steps to Be Taken in Case Material is Released or Spilled:** Keep sources of ignition and hot metal surfaces isolated from the spill. Material may flow slowly. Scrape into containers for disposal.

**Waste Disposal Methods:** Dispose of according to all local, state and federal regulations.

**Precautions to Be Taken in Handling and Storing:** Keep containers closed when not in use. Avoid breathing vapors and prolonged or repeated contact with skin. DO NOT handle or store near flame, heat or strong oxidants. Do not store in direct sunlight. Avoid prolonged storage above 35 deg C.

## **SECTION VIII: CONTROL MEASURES**

**RESPIRATORY:** Respiratory protection should not be needed. If exposure may or does exceed occupational exposure limits, respiratory irritation is experienced, or during spray application, use a properly fitted MSHA/NIOSH approved respirator fitted with ammonia & methylamine cartridges. In addition, spray application may require the use of paint pre-filters. If sanding or grinding on cured material, use above respirator fitted with HEPA filters or a dust mask.

**VENTILATION:** General mechanical ventilation is sufficient for most conditions. Local exhaust ventilation may be necessary for some operations.

**EYES:** Use chemical safety glasses, splash-proof eye goggles or goggles with full faceshield.

**CLOTHING/GLOVES:** Use nitrile or other chemical resistant gloves. Wear clean, long-sleeved, body covering clothing and rubber boots.

**OTHER PROTECTIVE EQUIPMENT:** The availability of eye washes and safety showers in work areas is recommended.

## **SECTION IX: TRANSPORT DATA**

**Proper Shipping Name:** Amines, liquid, corrosive, n.o.s. (modified cycloaliphatic amine)

**Hazard Class:** Corrosive Material - 8

**Identification Number:** UN 2735

**Packing Group:** III

## **SECTION X: DISCLAIMER**

CURAFLO MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO ANY INFORMATION PRESENTED HEREIN, ALL OF WHICH IS PROVIDED "AS IS". TO THE MAXIMUM EXTENT PERMITTED BY LAW, CURAFLO EXPRESSLY EXCLUDES ALL WARRANTIES, OBLIGATIONS, REPRESENTATIONS, LIABILITIES, TERMS AND CONDITIONS (WHETHER THEY ARE EXPRESS OR IMPLIED, OR ARISE IN CONTRACT, STATUTE, OR OTHERWISE, AND IRRESPECTIVE OF THE NEGLIGENCE OF CURAFLO, ITS EMPLOYEES OR AGENTS) IN CONNECTION WITH THE INFORMATION PRESENTED HEREIN. CURAFLO MAKES NO REPRESENTATIONS OR WARRANTIES AS TO MERCHANTABILITY, FITNESS FOR PURPOSE, NONINFRINGEMENT OR CONFORMITY WITH DESCRIPTION OR SAMPLE.